

IEEE-1394 STANDARDIZED APPARATUS AND
CONFIGURATION METHOD THEREIN

FIELD OF THE INVENTION

5 The present invention in general relates to an IEEE-1394 standardized apparatus and a configuration method.

BACKGROUND OF THE INVENTION

10 As image data or sound data transmission system, there exists the isochronous transmission system which is suitable for receiving and reproducing data simultaneously. As a serial bus standard characterized by isochronous transmission, there exists IEEE-1394 standard.

15 At a stage of developing applications based on this standard, a bus analyzer is occasionally connected to an IEEE-1394 serial bus so that various operations on the IEEE-1394 serial bus are analyzed. At this time, in order to adapt topology of the application development environment
20 to actual application usage environment, it is important that development tools such as a bus analyzer do not work as a node.

 In the IEEE-1394 standard, a PHY layer (physical layer) which does not work as a node is not defined. For this reason,
25 a PHY controller LSI having PHY function defined by the

IEEE-1394 standard is generally mounted into the bus analyzer which satisfies the IEEE-1394 standard.

However, when the bus analyzer mounted with the PHY controller LSI is connected to the IEEE-1394 serial bus, it is recognized as a node when topology is structured. For this reason, there arises a problem that the topology of the application development environment cannot be adapted to the actual application usage environment. Moreover, in the case of an application in which the topology is restricted, there arises a problem that a bus analyzer cannot be connected to the IEEE-1394 serial bus.

SUMMARY OF THE INVENTION

It is an object of this invention to provide an apparatus which can be connected to an IEEE1394 serial bus without recognizing the apparatus as a node. Moreover, another object of the present invention is to provide a configuration method for connecting the apparatus to the IEEE-1394 serial bus without recognizing the apparatus as a node.

The apparatus of the present invention according to the IEEE-1394 standard has a normal configuration control section which controls the configuration so that the apparatus is recognized as a node, and a non-node configuration control section which controls configuration

so that the apparatus is not recognized as a node. The normal configuration control section obtains a self physical ID and transmits a self_ID packet in a self-identification phase. The non-node configuration control section neither obtains
5 a self physical_ID nor transmits a self_ID packet in the self-identification phase, but transmits an ident done signal received from a child node directly to a parent node.

In addition, the apparatus of this invention has a PHY configuration packet output section for, when the apparatus
10 becomes a route node in a tree identification phase in a non-node mode, carrying out normal configuration and outputting a PHY configuration packet for resetting an apparatus of another node as a route node.

The apparatus of this invention can be connected to
15 the IEEE-1394 serial bus while the apparatus is not recognized as a node by another apparatuses connected to the IEEE-1394 serial bus.

In the configuration method of the present invention according to the IEEE-1394 standard, when a non-node mode
20 that an apparatus is not recognized as a node is specified and the apparatus is not a route node, the apparatus neither obtains a self physical_ID nor transmits a self_ID packet but transmits an ident_done signal received from a child node directly to a parent node.

25 Further, when the apparatus becomes a route node

regardless of the non-node mode, the apparatus obtains a
phisical_ID and transmits a self_ID packet, and generates
to output a PHY configuration packet for resetting an
apparatus of another node as a route node. In a normal mode
5 that the apparatus is recognized as a node, the apparatus
obtains a self phisical_ID and transmits a self_ID packet.

According to the method of this invention, the
apparatus can be connected to the IEEE-1394 serial bus while
the apparatus is not recognized as a node by another
10 apparatuses connected to the IEEE-1394 serial bus.

Other objects and features of this invention will
become apparent from the following description with
reference to the accompanying drawings.

15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a functional block diagram showing an
apparatus according to an embodiment of the present
invention.

Fig. 2 is a packet configuration diagram for explaining
20 a configuration of a PHY configuration packet generated in
the apparatus of the present invention.

Fig. 3 is a block diagram showing one example of a PHY
layer control LSI to which the apparatus of the present
invention is applied.

25 Fig. 4 is a chart showing a list of input/output

terminals of the PHY layer control LSI to which the apparatus of the present invention is applied.

Fig. 5 is a schematic diagram showing one example of a tree including the apparatus of the present invention.

5 Fig. 6 is a flow chart showing a configuration method according to the embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

One preferred embodiment of the present invention will
10 be explained below with reference to the attached drawings. The apparatus of the present invention will be explained first. The block diagram in Fig. 1 shows the functional configuration of the apparatus according to one embodiment of the present invention.

15 This apparatus conforms to the IEEE-1394 standard and has a 1394 signal input/output port section 1, a mode switching section 2, a non-node configuration control section 3, a normal configuration control section 4 and a PHY configuration packet output section 5. The 1394 signal
20 input/output port section 1 has at least two input/output ports, i.e., a port 0 and a port 1 in the shown example.
Another apparatuses to become a parent node and a child node are connected to these input/output ports respectively.

When the 1394 signal input/output port section 1 has
25 three or more ports and this apparatus is used in a non-

node mode, namely, the apparatus is not to be recognized as a node after the completion of configuration, only two input/output ports are valid in order to avoid topological discrepancy. Another apparatuses to become a high order node (parent node) or a low order node (child node) are connected to the valid two input/output ports. After the completion of the configuration, in the case of a mode that the apparatus is recognized as a node (hereinafter, the normal mode), a number of the valid input/output ports is not limited to two.

The mode switching section 2 switches input/output among the 1394 signal input/output port section 1, the non-node configuration control section 3 and the normal configuration control section 4 based on mode switching signals 6a and 6b supplied as mode switching unit. Namely, at the time of the non-node mode, the mode switching section 2 enables input/output of the non-node configuration control section 3 with respect to the 1394 signal input/output port section 1, and disables input/output of the normal configuration control section 4.

A process of self-identification phase is occasionally passed from the non-node configuration control section 3 to the normal configuration control section 4 due to internal factor. In this case, after the passing of the process, the input/output of the normal configuration

control section 4 is enabled, and the input/output of the non-node configuration control section 3 is disabled. The internal factor will be mentioned later.

In addition, at the time of the normal mode or in the case where the process is passed from the non-node configuration control section 3, the mode switching section 2 disables the input/output of the non-node configuration control section 3 with respect to the 1394 signal input/output port section 1. The mode switching section 2 enables the input/output of the normal configuration control section 4 with respect to the 1394 signal input/output port section 1.

The non-node configuration control section 3 controls configuration so that the apparatus is not recognized as a node in the non-node mode. That is, the non-node configuration control section 3 neither obtains a self physical_ID nor transmits a self ID packet in the self-identification phase, but transmits an ident done signal received from a child node directly to a parent node. As a result, the apparatus is not recognized as a node by another apparatus connected to the IEEE-1394 serial bus.

PASSES on
an ident done
signal from child
to a parent

However, when the apparatus becomes a route node in a tree identification phase, the non-node configuration control section 3 passes the process of the self-identification phase to the normal configuration control

section 4. This is the above-mentioned internal factor. At this time, the non-node configuration control section 3 transmits the mode switching signal 6b based on the internal factor to the mode switching section 2.

5 When taking over the process of the self-identification phase from the non-node configuration control section 3, the normal configuration-control-section 4 controls configuration so that the apparatus is recognized as a route node. That is, the normal configuration control
10 section 4 obtains a self phisical_ID and transmits a self_ID packet. Moreover, the normal configuration control section 4 transmits a signal which permits output of the PHY
configuration packet to the PHY configuration packet output
section 5.

15 In addition, the normal configuration control section 4 controls configuration so that the apparatus is recognized as a node in the normal mode similarly to another apparatuses on the IEEE-1394 serial bus. Namely, the normal configuration control section 4 obtains a self phisical_ID
20 and transmits a self_ID packet.

 When receiving a PHY configuration packet output permission signal from the normal configuration control section 4, the PHY configuration packet output section 5 generates a PHY configuration packet and outputs it to the
25 normal configuration control section 4. The PHY

configuration packet is generated so as to reset another
apparatus of a node other than the apparatus as a route node.

One example of the PHY configuration packet is shown
in Fig. 2. In Fig. 2, when the third field 11 from the left,
5 namely, a field on the right of a phisicial_ID (in the drawing,
phy_ID) field 12 is set (in the drawing, "R"), the apparatus
which receives this packet sets force root bit. Next,
reconfiguration is carried out, thereby restructuring the
topology.

10 At the time of the reconfiguration, the apparatus which
received the PHY configuration packet easily becomes a route
node because output of parent notify signal is delayed in
the tree identification phase. Therefore, an apparatus
other than the apparatus is set as a route node.

15 The mode switching signal 6a is generated by selecting
by a user of the apparatus as to whether or not the apparatus
is recognized as a node. Namely, the mode switching signal
6a is generated based on an external factor. For example,
the mode switching signal 6a is supplied from the outside
20 via a not shown external terminal. The mode switching
signal 6b is generated based on this internal factor.

The block diagram in Fig. 3 shows one example of the
PHY layer control LSI to which the apparatus having the above
structure is applied. This LSI has an arbitration control
25 section 21, two cable ports 22 and 23, a receipt data decoder

24, a transmit data encoder 25, a phase lock loop (PLL) 26,
a twisted pair bias generator 27, a link interface
input/output 28 and a cable power status section 29. The
arbitration control section 21, the cable ports 22 and 23,
5 the receipt data decoder 24 and the transmit data encoder
25 correspond to the structure of the part shown in Fig. 1.

In the example shown in Fig. 3, a Non_node terminal
20 is provided as one of input terminals. The Non_node
terminal 20 is connected to the arbitration control section
10 21. The mode switching signal 6a (see Fig. 1) which is
generated based on external factor is supplied to the
Non_node terminal 20. Since the other input/output
terminals are the same as those in a conventional PHY layer
control LSI, the list and description of the input/output
15 terminals are shown in Fig. 4, and the explanation of the
respective terminals is omitted.

The schematic diagram in Fig. 5 shows one example of
a tree configuration composed of four apparatuses including
the apparatus having the above structure. In the example
20 shown in Fig. 5, an apparatus 31 of a node A is a route node,
and its physical_ID (in the drawing, phy_ID) is "2".

An apparatus 32 of a node B and an apparatus 33 of a
node C are connected to a port 1 and a port 2 of the node
A respectively. The node B is a leaf node, and its
25 physical_ID is "0". The node C is a branch node, but a

physical_ID is not given to the node C. An apparatus 34 of a node D is connected to a child port of the node C, and it is a leaf node. A physical_ID of the node D is "1".

The apparatus 33 of the node C is the apparatus having the structure shown in Fig. 1, and is, for example, a bus analyzer. The apparatus of the node C is not recognized as a node by the other apparatuses (node A, node B and node C). Namely, in the tree structure shown in Fig. 5, two leaf nodes (B and D) are connected to the node A in appearance. The bus analyzer is used to be connected to IEEE-1394 serial bus to analyze various operations on the IEEE-1394 serial bus when applications are developed.

Next, a configuration method of the present invention will be explained below. Fig. 6 is a flow chart showing the configuration method according to the present invention. When configuration is started, at first a process for judging a mode specified by user's setting (external factor) is executed (step S1). When the result of the judgment is the non-node mode, the mode switching section 2 enables the input/output of the non-node configuration control section 3. As a result, the non-node configuration control section 3 is connected to the 1394 signal input/output port section 1.

Next, the IEEE-1394 serial bus is initialized (step S2) and the tree is identified (step S3). Thereafter, a

judgment is made as to whether or not the apparatus is the route node in the tree identification process (step S4).

When the apparatus is not the route node, a non-node self-identification process (step S5) is executed, and the
5 configuration is completed. Details of the non-node self-identification process will be mentioned later.

Meanwhile, when the apparatus is the route node, the internal factor of the mode switching is generated. For this reason, the self-identification phase process is passed to
10 the normal configuration control section 4. Therefore, the mode switching section 2 enables the input/output of the normal configuration control section 4, and connects the normal configuration control section 4 to the 1394 signal input/output port section 1. The input/output of the
15 non-node configuration control section 3 is disabled.

The normal configuration control section 4 executes a normal self-identification process (step S6) so that the apparatus is recognized as a node. This normal self-identification process is the same as the conventional
20 process. Thereafter, the normal configuration control section 4 permits the PHY configuration packet output section 5 to output the PHY configuration packet. The PHY configuration packet output section 5 outputs the PHY configuration packet (see Fig. 2) based on the output permission (step S7). As a result, the above-mentioned
25

configuration method is carried out repeatedly until the topology is structured without recognizing the apparatus as a node, and the topology is tried to be reconstructed.

When the normal mode is specified by the external factor, the mode switching section 2 enables the input/output of the normal configuration control section 4, and connects the normal configuration control section 4 to the 1394 signal input/output port section 1. Thereafter, the IEEE-1394 serial bus is initialized (step S8), and a tree identification process (step S9) and a normal self-identification process similar to the conventional process (step S10) are executed successively, and the configuration is completed.

Here, the bus initializing process and the tree identification process at steps S8 and S9 are the same as the bus initializing process (step S2) and the tree identification process (step S3) in the non-node mode. Therefore, in the non-node configuration control section 3 and the normal configuration control section 4 shown in Fig. 1, one hardware can be commonly used for executing the bus initializing process and the tree identification process.

Next, details of the non-node self-identification process are explained below. For easy description, the explanation will refer to the tree structure shown in Fig. 5 as an example, but the present invention is not limited

to this tree structure. The node A which becomes a route
node in the tree identification process in the non-node mode
(Fig. 6, step S3) passes the control to a child node connected
to the smallest-numbered port. In the example shown in Fig.
5, the node A passes the control to the node B connected to
the port 1.

The node B is not connected to a node other than the
node A. Namely, a child node does not exist for the node
B. Therefore, the node B obtains "0" as a self physical_ID,
and transmits a self_ID packet. Thereafter, the node B
transmits an ident_done signal to the node A as a parent node.

When receiving the ident_done signal from the node B,
the node A passes the control to a child node connected to
a port with a number next smaller than that of the node A.
In the example shown in Fig. 5, the node A passes the control
to the node C connected to the port 2. The node C is connected

also to the node D as well as the node A. Therefore, the
node C passes the control to the node D.

A child node does not exist in the node D. Moreover,
the node D receives one self_ID packet. Therefore, the node
D obtains "1" as the self physical_ID, and transmits a self_ID
packet. Thereafter, the node D transmits an ident_done
signal to the node C as a parent node.

Since the non-node mode is specified in the node C,
when receiving the ident_done signal from the node D, the

node C transmits the ident_done signal directly to the node

A. Namely, in the non-node mode, the node C neither obtains a self_physical_ID nor transmits a self_ID packet. In the

normal mode, the node C obtains a self_physical_ID and

5 transmits a self_ID packet, and transmits an ident_done signal to the parent node.

When the node A as a route node receives the ident_done signal, which is generated by the node D, from the node C, it means that the node A receives the ident_done signals via
10 all the ports. A number of the ident_done signals received by the node A is two. Therefore, the node A obtains "2" as the self_physical_ID, and transmits the self_ID packet. As a result, the non-node self-identification process is completed. Since the node C does not have a physical_ID,
15 it is not recognized by the other nodes.

According to the above embodiment, the non-node configuration control section 3 and the normal configuration control section 4 are provided and output of any one of them can be selected. In the non-node mode, the non-node
20 configuration control section 3 neither obtains a self_physical_ID nor transmits a self_ID packet, but transmits the ident_done signal received from the child node directly to the parent node.

For this reason, the apparatus is not recognized as
25 a node by the other nodes. Namely, the apparatus can be

connected to the IEEE-1394 serial bus while the apparatus
is not recognized as a node by the other apparatuses.
Therefore, when this apparatus is used as a bus analyzer,
the apparatus is effective in the quality of the application
5 system development and in reducing TAT.

The present invention is not limited to the above-
mentioned embodiment, and its design can be variously
changed. For example, in the structure shown in Fig. 3, the
mode switching signal 6a is supplied to the Non_node terminal
10 20. However, a register for storing a result that the
non-node mode or the normal mode is selected by a user is
newly provided in the PHY layer control LSI, and the
configuration may be carried out in one of the modes based
on the value of the register.

15 According to the apparatus of the present invention,
the apparatus has the normal configuration control section,
which obtains the self physical_ID and transmits the self_ID
packet so that the apparatus is recognized as a node, and
the non-node configuration control section, which [neither
20 obtains the self physical_ID nor transmits the self_ID
packet] so that the apparatus is not recognized as a node,
but transmits the ident_done signal received from the child
node directly to the parent node. For this reason, the
apparatus can be connected to the IEEE-1394 serial bus while
25 the apparatus is not recognized as a node by the other

apparatuses connected to the IEEE-1394 serial bus.

According to the configuration method of the present invention, the apparatus, which is not to be recognized as a node in the non-node mode, neither obtains the self physical_ID nor transmits the self_ID packet, and transmits the ident_node signal received from the child node directly to the parent node. Meanwhile, since the apparatus, which is recognized as a node in the normal mode, obtains the self physical_ID and transmits the self_ID packet, the apparatus can be connected to the IEEE-1394 serial bus while the apparatus is not recognized as a node by the other apparatuses connected to the IEEE-194 serial bus.

Although the invention has been described with respect to a specific embodiment for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art which fairly fall within the basic teaching herein set forth.